



# PRODUCT SPECIFICATION

Revision:1  
Date:2011-7-1  
Page: 1/1

## Battery for Crane Remote Control

### AF-FUB10MB



Models

HBC® FUB10AA/XL

#### Compatibility

**Battery Model:** BA211060

#### Physical Characteristics

**Dimension:** 150.2 X 56.5 X 19.7 mm (5.91 X 2.22 X 0.78 inch)

**Weight:** 330 g (11.64 oz.)

**Plastic Material:** ABS

#### Electrical Characteristics

**Chemistry:** Ni-MH

**Voltage:** 2 X 6.0V

**Capacity:** Typical: 1500mAh; Minimum: 1450mAh

**Cell:** JJJ J-AA1500A

#### Operation Specification

**Charging Voltage:** 7.0 ~ 9.5 V

**Charging Current:** 0.2 ~ 2.0C

**Discharging Current:** 0.2 ~ 2.0C

**Discharging End Voltage:** 5.0 V

#### User Environment

**Charging Temperature:** ± 0 ~ +40°C (+32 ~ +104°F)

**Discharging Temperature:** -20 ~ +50°C (-4 ~ +122°F)

**Storage Temperature:** -20 ~ +50°C (-4 ~ +122°F)

**Prolonged Storage Temp.:** -20 ~ +35°C (-4 ~ +95°F)

Brand names are registered trademark of their respective owners

**Advantech Limited**

www.advantech.com  
sales@advantech.com